

Automatic Extinguisher Clean Agent Gas

FBA-G4

4 kg (6.8 m³ enclosed volume)

FBA-G6

6 kg (10.2 m³ enclosed volume)



Flammable
Liquids



Flammable
Gas



Electrical
Risks

Used to protect machinery / plant and where there is a risk of fire such as in boat / engine bays, flammable products storage areas. Ideal for use in sensitive locations and are a suitable option to protect high-value assets such as precious items storage, computing technology and telecommunications facilities. The unit required is determined by the gross volume of that compartment. Only one unit should be installed in any one compartment and should provide the total protection required for that compartment. The compartment should have no unnecessary ventilation that would allow needless loss of suppressant.

- **CLEAN AGENT (HALON REPLACEMENT).**
- **ZERO OZONE DEPLETION.**
- **5 YEAR WARRANTY.**
- **SUITABLE FOR B AND C CLASS FIRES.**
- **SAFE FOR USE ON ELECTRICAL EQUIPMENT.**
- **SUPPLIED WITH BRACKET.**

Model	FBA-G4	FBA-G6
Capacity	4 kg	6 kg
Total Weight	2.14 kg	3.10 kg
Total Height	295 mm	305 mm
Total Width (incl. bracket)	270 mm	300 mm
Working Temp.	-30° to +60°C	
Discharge Time / Temp.	Under 10 secs @ 79°C ± 5°C	
Maximum Volume Protected	6.8 m ³	10.2 m ³
Operating Pressure	12 bar @ 20°C	
Minimum Burst Pressure	55 bar	